NEW

DOLCECLIMA® Compact

OLIMPIA SPLENDID
HOME OF COMFORT

Designed in Italy

DOLCECLIMA COMPACT Model# 2150

FEATURES

Capacity:10,000 btu/h
Sound Power: dBA 62

EER: 8.47
Refrigerant: R-32
Automatic Condensation Disposal - No Tank
Multifunction Remote: Wireless Control
Display: LED
Timer: 12h
Extras: Convenient Side Handles & Casters

FUNCTIONS

Fan mode: Adjustable 2 fan speed. Fan only mode is also available.

Dehumidification mode: Reduces airflow to increase the amount of moisture removed from the space.

Auto mode: Automatic operation which regulates cooling in relation to the ambient temperature to optimize energy consumption.

Sleep mode: Gradually increases the temperature setpoint to reduce noise for greater comfort at night.

Turbo mode: Maximum fan speed, Extra Cooling

COMPACT TECHNOLOGY
Only 27.7" high, 13.6" wide and 14" deep allows greater flexibility when chosing locations.

REMOTE CONTROL
User-friendly remote control. Fast and easy to set of all functions.

EASY TO MOVE BETWEEN ROOMS
Practical rotating castors allow effortless moving from one room to another.

BEST INDUSTRY WARRANTY 3 Yrs. FULL 3 YEAR WARRANTY

c UL us

Design Specifications and Capacities*		Dolceclima Compact
Model Number		2150
Voltage (min 98, max 127)	AC Volts-Phase-Hertz	115-1-60
Rated Capacity for Cooling [1]	BTU/H	10,000
Thermostat Off Mode Power Consumption	Watts	130
Maximum Power Consumption [2]	Watts	1180
Energy Efficiency Ratio	EER	8.47
Dehumidification Capacity	Pints/Hr.	2.9
Compressor Rated Load Amps Lock Rotor Amps	Type R.L.A. L.R.A.	Rotary 7.4 43
Indoor Fan Speeds Full Load Amps	Type # of speeds F.L.A.	Centrifugal 2 1.6
Indoor Air Volume (2 speeds)	CFM (H,L)	206/153
Flexible Pipe (Included in Box)	Length (in feet) Diameter (in inches)	5’ 6”
Maximum Remote-Control Range Maximum Angle	Feet Degrees	26' 80°
Dimensions (without packaging)	W/H/D	13.6" x 27.7" x 14.0"
Dimensions (with packaging)	W/H/D	14.8" x 34.5" x 15.8"
Weight (without packaging)	lbs	52.9
Weight (with packaging)	lbs	61.7
Sound Level [3]	dBA min/max	51/55
Refrigerant	ASHRAE #	R-32
Refrigerant Factory Charge	oz	10.6
Maximum Operating Pressure	PSI	550
Maximum Operating Pressure (low side)	PSI	340

Design Condition Parameters*			Unico Smart 12 HP
Indoor Temperature	Maximum Operating Temperature	°F/°C	DB 95°F/35°C - WB 75°F/24°C
	Minimum Operating Temperature	°F/°C	DB 62°F/17°C
Outdoor Temperature	Maximum Operating Temperature	°F/°C	DB 109°F/43°C - WB 90°F/32°C
	Minimum Operating Temperature	°F/°C	DB 61°F/16°C

* Values may change if models are revised. Always use the latest publication date for any literature.

(1) Test conditions:Data refers to conditions and parameters as required by DOE requirements governing this product type.
Outdoor Ambient Temperature DB 95°F/35°C - WB 75°F/24°C
Indoor Ambient Temperature DB 81°F/27°C - WB 66°F/19°C

(2) Highest load test in cooling mode

(3) The sound pressure level has been measured into half-anechoic room at 3.3 feet (1m) with respect to the front of the unit with a microphone at 3.3 feet (1m) in height.

Pub#US002.06022019